



# SUS304 304(鋼種)・HSK(製造業者名)マーク付き六角ボルト (JIS B 1180 附属書)

材料は新日鐵住金ステンレス㈱と大同特殊鋼㈱の「JIS G 4308 ステンレス鋼線材」を使用しています。

## 在庫サイズ

	M5	M6	M8		M10		M12		M14		M16		M20		M22		M24		
規格	8×3.5	10×4	13×5.5		17×7		19×8		22×9		24×10		30×13		32×14		36×15		規格
ピッチ	0.8	1.0	1.25		1.5		1.75		2.0		2.0		2.5		2.5		3.0		ピッチ
半径 ネジ長さ	-	-	-	30	-	26	-	30	-	34	-	40	-	46	-	50	-	54	半径 ネジ長さ
全・半 区分	全	全	全	半	全	半	全	半	全	半	全	半	全	半	全	半	全	半	全・半 区分
8	○	○																	8
10	○	○	○																10
12	○	○	○																12
14	○	○	○																14
15	○	○	○		○														15
16	○	○	○		○														16
18	○	○	○																18
20	○	○	○		○		○												20
22	○	○	○																22
25	○	○	○		○		○		○		○								25
30	○	○	○		○		○		○		○		○						30
35	○	○	○		○	○	○		○		○		○						35
40	○	○	○		○	○	○	○	○	○	○		○						40
45	○	○	○		○	○	○	○	○	○	○	○	○						45
50	○	○	○		○	○	○	○	○	○	○	○	○	○					50
55		○	○	○	○	○	○	○		○	○	○	○	○	○				55
60		○	○	○	○	○	○	○		○	○	○	○	○	○				60
65		○	○	○	○	○	○	○		○	○	○	○	○	○				65
70		○	○	○	○	○	○	○		○	○	○	○	○	○				70
75		○	○	○	○	○	○	○		○	○	○	○	○	○				75
80		○	○	○	○	○	○	○		○	○	○	○	○	○				80
85		○	○	○	○	○	○	○		○	○	○	○	○	○				85
90		○	○	○	○	○	○	○		○	○	○	○	○	○				90
95			○	○	○	○	○	○		○	○	○	○	○	○				95
100		○	○	○	○	○	○	○		○	○	○	○	○	○				100
110			○	○	○	○	○	○		○	○	○	○	○	○				110
120			○	○	○	○	○	○		○	○	○	○	○	○				120
130			○	○	○	○	○	○		○	○	○	○	○	○				130
140			○	○	○	○	○	○		○	○	○	○	○	○				140
150			○	○	○	○	○	○		○	○	○	○	○	○				150